

EMPROTEC SHPD PLUS 15W-40 (Export)

Product Code: HDD035 | **Revision:** 20231101



Available Pack Sizes

Applications

A premium multi grade heavy duty engine oil manufactured from high-quality solvent refined base oils and a performance enhancing additive package. The produces a high-viscosity, superb multipurpose engine oil suitable for both petrol and diesel fuelled vehicles. Incorporating our specialist Adaptive Molecular Technology to enhance the power and efficiency of your vehicle to help maintain peak reliability to ensure maximum performance in mixed fleet applications.

Recommended by Aztec Oils as suitable for the following applications

ACEA E7 (E5, E3)
API CI-4/SL
Deutz DQC III-10
Global DHD
JASO DH-1
Mack EO-N
MAN M 3275
Mercedes-Benz 228.3
MTU Type 2
Renault RLD, RLD-2
Volvo VDS-3
Suitable for DAF, Scania & Perkins

Benefits

- Anti-wear performance for reduced engine wear.
- High shear stability for stay in grade performance.
- High thermal stability provides protection against piston deposits.
- Ideal mixed fleet lubricant.
- Improved bore polishing protection.
- Powerful detergent & dispersant technology.

Typical Test Data

Density @ 15°C	ASTM D4052	0.87
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	105
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	14.3
Pour Point (°C)	ASTM D97	-30
Total Base Number (mg KOH/g)	ASTM D2896	13
Viscosity Index	ASTM D2207	139

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- When disposing of the product after use, please protect the environment and comply with local regulations.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.