

MOTOTEC CLASSIC 20W-50

Product Code: MOT022 | **Revision:** 20240819



Mineral oil based low detergent classic motorcycle engine oil.

Available Pack Sizes



Applications

A specialist mineral based multigrade lubricant recommended for use in veteran and classic motorcycle engines without modern oil filtration systems which would traditionally use a monograde SAE 30, 40 or 50. Provides high levels of anti-wear protection to vital engine and transmission components, whilst maintaining low levels of detergency to allow dirt and debris to fall to the bottom of the engine and into the sump. Compatibility with dry and wet clutches ensures smooth, reliable gear changes.

Recommended by Aztec Oils as suitable for the following applications

API SF, SE
Suitable for BMW, Harley Davidson, Metric, Norton, Triumph & Yamaha.

Benefits

- Designed for veteran & classic motorcycles with combined or separate transmission & chain case.
- Excellent anti-wear characteristics.
- High viscosity helps to reduce oil loss & leakage.
- Multigrade viscosity allows for easier starting & improved low temperature performance.
- Low levels of detergency & dispersancy.
- Suitable for air & liquid cooled 4-stroke engines.

Typical Test Data

Appearance		Clear & bright, amber
Density @ 15°C (kg/m ³)	ASTM D4052	0.883
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	165
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	18
Pour Point (°C)	ASTM D97	-20
Total Base Number (mg KOH/g)	ASTM D2896	5
Viscosity Index	ASTM D2207	120

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.